SATURN SW

1000 x 256 - 30 µm pitch - MCT

 \rightarrow The High resolution detector for SWIR hyperspectral imaging and spectroscopy.





Saturn SW is a very high-performance and high-resolution IDCA which enables you imaging from 0.8 to 2.5 µm.

This IDCA is well-adapted to low flux in this wavelength range and the line by line gain selection function makes it perfectly suitable for hyperspectral imaging.

This high-performance IDCA takes full advantage of Sofradir's state of the art technologies.

ARRAY FEATURES

Format	1000 x 256
Pixel pitch	30 µm x 30 µm
Detector spectral response	0.8 μm – 2.5 μm
FPA Operating temperature	Up to 200 K

ROIC (READ-OUT INTEGRATED CIRCUIT)


ROIC architecture	Snapshot operation, Integrate-While-Read mode	
ROIC functionalities	Programmable integration time, programmable gain, anti-blooming system	
Windowing modes	Selectable lines to be read (user configurable)	
Gain selection	Selectable by lines (user configurable)	
Charge handling capacity	0.5 10 ⁶ e- (Gain 1) / 2.5 10 ⁶ e- (Gain 2) for 100% well fill	
Electrical dynamic range	> 3 V	
Readout noise	< 150 e- (for 0.5 10 ⁶ e- Gain 1); < 350 e- (for 2.5 10 ⁶ e- Gain 2)	
Signal outputs	4 or 8	
Pixel output rate	Up to 8 MHz per output	
Frame rate	Up to 240 Hz full frame rate	



SATURN SW

1000 x 256 - 30 µm pitch - MCT

→ The High resolution detector for SWIR hyperspectral imaging and spectroscopy.





TYPICAL^[*] PERFORMANCES

NETD	> 800 (for 2.5 10^{6} e- Gain 2, 50% well fill, 50 Hz)
Array operability	99.5%
Non uniformity	< 7%
Linearity	> 99.5%
Quantum efficiency	> 60% without antireflective coating

	LS 10-11i
FOV	TBD in function of user need
Regulated input power	< 10 WDC (**)
Cooldown input power	< 50 WDC (**)
Cooldown time	< 8 min
Weight	< 2.2 kg
Operating temperatures	- 40° C to 71° C

(*) Optional extended waveband : 40% α 0.5 μm, 75% α 0.8 μm, >80% from 0.9 μm to 1.6 μm (**) WDC = at cooler C&CE DC input

OPTIONS


PRO(G -5809 - © Sofradir - December 2015

Proximity driving electronics (including ADC) Technical training and support

APPLICATIONS



Exclusive Distributor - North America





SOFRADIR-EC 373 Route 46W, Fairfield, NJ 07004 USA Phone: 973-882-0211 Fax: 973-882-0997 Email: info@sofradir-ec.com www.sofradir-ec.com

