


# Pico1024Gen2™

1024 x 768 - 17 μm



## DESIGNED FOR HIGH DEFINITION INFRARED IMAGING

Designed for the most demanding environments, Pico1024Gen2 offers high resolution and high contrast imaging for long range detection applications.



SURVEILLANCE  
& UAV



DEFENSE




THERMOGRAPHY

- + OUTSTANDING IMAGE QUALITY
- + PROVEN RELIABILITY
- + SEAMLESS INTEGRATION

# Pico 1024Gen2™

1024 x 768 - 17 μm



**DESIGNED FOR  
HIGH DEFINITION  
INFRARED IMAGING**

## OUTSTANDING IMAGE QUALITY

**"Detects fast moving objects"**

- Sharp contrast
  - 30 mK < Thermal sensitivity < 50mK (F/1, 300K, 30Hz)
  - Extended operating temperature [-40°C; +85°C]
- Fluid and smooth image
  - Frame rate up to 120Hz
  - Thermal time constant < 12 ms
- High uniformity
  - Array operability > 99.5 %
  - Scene dynamic > 100°C

## PROVEN RELIABILITY

**"Robust for extreme environments"**

- Standards MIL810 - MIL 883
- Thermal Weapon Sight (TWS) qualified
- Product availability and exportability
  - Products designed and manufactured in Europe
- Product delivery to our customers
  - On-time order deliveries > 95%


## SEAMLESS INTEGRATION

**"Ready for high volume production"**

- Flexible configuration
  - Full access to sensor features through serial link
  - External frame synchronization capability
- Simplified image processing
  - TEClass, Shutterless compatible
  - Single gain table and predictable offset management for reduced calibration time
- Battery optimization
  - Low power consumption < 220 mW



### Recognition distance for vehicle 2.3 m x 2.3 m



Specifications are subject to change

**Exclusive Distributor  
North America**

**SOFRADIR-EC**  
373 Route 46W  
Fairfield, NJ 07004 USA  
Phone: 973-882-0211  
Fax: 973-882-0997  
Email: info@sofradir-ec.com