ThermEye[™]-b90 ThermEye[™]-b120


A disruptive thermal sensor technology for smart buildings.



ThermEye[™]-b90



ThermEye[™]-b120



Protects privacy



Day / Night



Multifunctional



Long battery



Large area

- Multifunctional sensor (detection, tracking, people counting)
- Very Low Power and compact
- Large area covered

Ideal for...

- > Space management: occupancy data tracking for optimal use of square meterage
- > Energy management: real-time data analysis for lower energy bills
- > Safety: hotspot detection for fire prevention
- > Security: intrusion detection

Plus points

- > Nonintrusive and anonymous
- > Ideal for wireless/IoT solutions



Exclusive Distributor North America

SOFRADIR-EC 373 Route 46W Fairfield, NJ 07004 USA Phone: 973-882-0211 Fax: 973-882-0997 Email: info@sofradir-ec.com www.sofradir-ec.com



ThermEye[™]-b90 ThermEye[™]-b120



Performance

80 x 80 pixel thermal sensors (LWIR microbolometer technology)

Operating temperature: -10°C to +50°C

Wide field of view: HFOV 90° or HFOV 120°



Flexibility

Continuous mode from 1 Hz to 100 Hz

Intermittent mode for very low power applications (e.g. 1 frame/min)

Surface Mount Device BGA(*), compliant with reflow process (IPC/JEDEC J-STD-020E)

HSync/VSync clocking

Full digital (integrated ADC and DAC)

(*)Ball Grid Array

Long battery life

Power consumption ≤ 55 mW (continuous mode)

In intermittent mode @ 1 frame/2min 1 battery AA lasts for 5 years

Compact form factor

Dimensions (mm): 14 x 14 x 9

Weight < 2g

	Product number	HFOV
ThermEye™-b90	M80L90	90°
ThermEye [™] -b120	M80L120	120°





Exclusive Distributor North America SOFRADIR-EC 373 Route 46W Fairfield, NJ 07004 USA Phone: 973-882-0211 Fax: 973-882-0997 Email: info@sofradir-ec.com

www.sofradir-ec.com