





AstroScope™

for Nikon and Canon Mirrorless Cameras

FOR EXPORT ONLY

NIGHT VISION ADAPTER

Convert your high-performance Nikon and Canon Mirrorless camera and lens into a military grade night vision system for video and image capabilities. Enabling your Mirrorless camera with GEN-3 night vision technology. Transform dark scenes into bright, high-resolution images. AstroScopeTM is an essential tool for today's night vision photographer.

ENHANCE YOUR VISIBILITY IN LOW LIGHT / NO LIGHT

- MILITARY-GRADE NIGHT VISION
- ENHANCES EQUIPMENT YOU ALREADY USE
- WHITE PHOSPHOR OR GREEN PHOSPHOR OPTIONS
- QUICK CONNECT/DISCONNECT, NO CABLES OR CHARGING
- VARIABLE GAIN ADJUSTMENT FOR VARIED CONDITIONS

SURVEILLANCE

LEISURE

DEFENSE







•• CONVERT YOUR MIRRORLESS CAMERA INTO A HIGH-PERFORMANCE NIGHT VISION SYSTEM ●•







Law Enforcement



Surveillance



Wildlife Management









CANON EOS RF MOUNT MIRRORLESS CAMERA + ASTROSCOPE™ CONFIGURATION



NIKON Z-MOUNT MIRRORLESS CAMERA + ASTROSCOPE™ CONFIGURATION

 $\textbf{Without} \ \mathsf{AstroScope}^{\mathsf{TM}}$



 $\textbf{With} \ \mathsf{AstroScope}^{\mathsf{TM}}$

V	vitn Astro	Scope	
	<u>ata</u>)		•
	(P)		ale de
	200101-000		

Both shots were taken using the same camera settings

Shutter Speed: 1/40; No Flash; Lens Aperture: F/5; Focal Length: 52 mm; ISO: 800; Exposure Comp: 0

Manufacturing Time: 4-6 Weeks, not including shipping. Call for pricing.

Export of this product is controlled by the U.S. Department of State with ITAR requirements. Prior authorization is required for export or transfer.

LYNRED HEADQUARTERS DEVELOPMENT & PRODUCTION CENTER

Actipole - CS 10021 - 364, route de Valence 38113 Veurey-Voroize - France Phone +33 (0)4 76 28 77 00 info@lynred.com

LYNRED ASIA PACIFIC	;
PTE LTD	

5 Shenton Way, #22-04 UIC Building 068808 Singapore info@lynred.com

GENERAL SPECIFICATIONS Device Weight ■ 574a* Dimensions ■ 6.95 cm x 12.78 cm Intensifier ■ Generation 3 mil-spec, 18 mm GaAs, MCP Lifetime >12.000 hours continuous use Power Requirements <300mW (<50mA typical)</p> Lens Compatibility RF Mount (Canon), Z Mount (Nikon) Frame ■ Full, 1.6 (Canon), FX, DX (Nikon) Warranty ■ 1 Year, workmanship and materials

*Typical

FEATURED PRODUCTS							
PRODUCT DESCRIPTION	CANON/NIKON	BODY TYPE	PHOSPHOR	GAIN			
9400EOS-3VM-1600WP	EOS	MIRRORLESS	WHITE	VARIABLE			
9400EOS-3VM-1800WP	EOS	MIRRORLESS	WHITE	VARIABLE			
9400EOS-3VM-2000WP	EOS	MIRRORLESS	WHITE	VARIABLE			
9400EOS-3VM-2200WP	EOS	MIRRORLESS	WHITE	VARIABLE			
9400EOS-3VM-1600GP	EOS	MIRRORLESS	GREEN	VARIABLE			
9400EOS-3VM-1800GP	EOS	MIRRORLESS	GREEN	VARIABLE			
9400EOS-3VM-2000GP	EOS	MIRRORLESS	GREEN	VARIABLE			
9400EOS-3VM-2200GP	EOS	MIRRORLESS	GREEN	VARIABLE			
9400NIKSP-3VM-1600WP	NIK	MIRRORLESS	WHITE	VARIABLE			
9400NIKSP-3VM-1800WP	NIK	MIRRORLESS	WHITE	VARIABLE			
9400NIKSP-3VM-2000WP	NIK	MIRRORLESS	WHITE	VARIABLE			
9400NIKSP-3VM-2200WP	NIK	MIRRORLESS	WHITE	VARIABLE			
9400NIKSP-3VM-1600GP	NIK	MIRRORLESS	GREEN	VARIABLE			
9400NIKSP-3VM-1800GP	NIK	MIRRORLESS	GREEN	VARIABLE			
9400NIKSP-3VM-2000GP	NIK	MIRRORLESS	GREEN	VARIABLE			
9400NIKSP-3VM-2200GP	NIK	MIRRORLESS	GREEN	VARIABLE			

Additional parts upon request.

LYNRED USA

373 US Highway 46W Fairfield, NJ 07004, USA Phone +1 973.882.0211 info@lynred-usa.com NIT (New Imaging Technologies)
Premium SWIR by LYNRED

1 impasse de la Noisette 91370 Verrières-le-Buisson - France Phone +33 1 64 47 88 58

info@new-imaging-technologies.com

ZUZAGLINIELU. Versioni, Zu dateo Navember / ¿ZUZE-, intocasi entry images & L'INNELL. Disalizi n'i CUMMA. Technical characteristics described in this data sheet are for information only. They are not contractual and may change without prior notice.